



## Dealer Bulletin

March 22<sup>nd</sup> 2005

**Reference:** Chassis/Suspension settings and tyre pressures.

**Vehicles:** All models.

**Bulletin No:** 1009

Given below are revised chassis settings and tyre pressures for all models. They can be applied to all the models listed.

### CERBERA, TUSCAN (ALL), TAMORA & T350

	FRONT	REAR
TOE SETTINGS	0 - 1.5 mm IN (0 -10 minutes IN)	3.0mm IN (22 minutes IN)
CAMBER SETTINGS	0.5 -0.75° Negative	1.25° Negative

NB: The toe settings given are axle values, NOT single wheel values. Divide figures given by two to get wheel value.

TYRE PRESSURES	FRONT	REAR
Normal driving.	28 psi (1.93 bar)	28psi (1.93 bar)
Sustained high speed or fully laden.	31 psi (2.14 bar)	31 psi (2.14 bar)

NB: The tyre pressures given here are for 16 and 18 inch wheels and tyres.

### SAGARIS

	FRONT	REAR
TOE SETTINGS	0 - 1.5 mm IN (0 -10 minutes IN)	3.0mm IN (22 minutes IN)
CAMBER SETTINGS	0.5 -0.75° Negative	1.50° Negative

NB: The toe settings given are axle values, NOT single wheel values. Divide figures given by two to get wheel value.